

WC095 Installation Instruction Guidelines



Remove the rear frame from the back of the WC pan (3 bolts either side) and attach to the wall. Screws can be screwed through the four captive nuts into suitable wall fixing plugs. (wall fixings not supplied).



The supplied plastic concealed cistern is pre fitted with the inlet valve and syphon. The inlet valve can be changed to the opposite side if required.

The concealed plastic cistern is mounted to the inside of the cistern enclosure onto the three studs and secured with the three nuts and washers.



Cistern shown fitted.



Fit the dual flush push button to the hole in the front of the cistern enclosure. The chrome bezel unscrews from the front and the button is inserted from behind. The large plastic collar then tightens up from behind. Fit the two air tubes from the syphon to the rear of the push button. Instructions are included in the plastic concealed cistern.



Place the cistern enclosure onto the top of the WC pan. Remove the side access panels from both sides of the toilet.

Trim the 90 degree flush bend to size and fit to the toilet with the flush pipe connector supplied connect to the cistern with the syphon nut and washer supplied with the cistern.

Secure the cistern enclosure to the toilet with the four bolts and washers supplied.

Connect your inlet pipe work to the inlet on the side of the cistern and leave a connection tail out of the bottom of the cistern enclosure.

Put to complete toilet into place over the rear frame already attached to the wall. Connect the trap from the toilet into your soil pipe using a suitable WC connector (not supplied).

Connect your inlet pipework to the tail left at the bottom of the cistern enclosure.

Secure the toilet to the wall frame with the six bolts. There are also fixing holes for wall fixing at the top of the cistern enclosure.

Turn on the water supply and test for proper function and leaks.

Finally fit the plastic cistern lid to the plastic cistern and fit the stainless steel lid to the cistern enclosure with the two bolts supplied.

Please note:

These instructions are for guidance only and no responsibility is taken for accuracy. They are meant purely as a guideline.

We do not accept responsibility for any problems that may occur through the use of these instructions.

These toilets should only be installed by a qualified plumber with the relevant experience and insurance.

Warning! Please check for any hidden pipes or electrical cables before drilling holes in the floor or walls.

When using power tools always follow the manufacturer's user instructions.